


Dished End

Flange

The Dished End program is a product line designed to enhance the mixing performance when dealing with smaller vessels.



Specifications


Item number	Description	øA mm (in)	øB mm (in)	C mm (in)	Mixer
D20FN3-L05018	Dished End ID200. Flange. 1" NA TOV	200 (7.87)	210 (8.27)	66.6 (2.62)	ZG2 / HS2 / HP2
D20FR3-L05019	Dished End ID200. Flange. 1" RA TOV	200 (7.87)	210 (8.27)	68.0 (2.68)	ZG2 / HS2 / HP2
D25FN3-L05016	Dished End ID250. Flange. 1" NA TOV	250 (9.84)	260 (10.24)	70.9 (2.79)	ZG2 / HS2 / HP2
D25FR3-L05017	Dished End ID250. Flange. 1" RA TOV	250 (9.84)	260 (10.24)	72.3 (2.85)	ZG2 / HS2 / HP2
D30FN3-L05014	Dished End ID300. Flange. 1" NA TOV	300 (11.81)	310 (12.20)	75.2 (2.96)	ZG2 / HS2 / HP2
D30FR3-L05015	Dished End ID300. Flange. 1" RA TOV	300 (11.81)	310 (12.20)	76.6 (3.02)	ZG2 / HS2 / HP2

Specifications. Add-ons

Description	D mm (in)	D-1 mm (in)	D-2 mm (in)	D-3 mm (in)	D-4 mm (in)	E/E-1/E-2 mm (in)	E-3 mm (in)	E-4 mm (in)
D20FN3-L05018	101.1 (3.98)	118.1 (4.65)	121.1 (4.77)	152.4 (6.0)	160.9 (6.33)	7.7 (0.30)	35.3 (1.39)	43.8 (1.72)
D20FR3-L05019	101.0 (3.98)	118.0 (4.65)	121.0 (4.76)	152.3 (6.0)	160.8 (6.33)	7.2 (0.28)	34.8 (1.37)	43.2 (1.7)
D25FN3-L05016	126.1 (4.96)	140.6 (5.54)	146.1 (5.75)	177.4 (6.98)	185.9 (7.32)	7.7 (0.30)	35.3 (1.39)	43.8 (1.72)
D25FR3-L05017	126.0 (4.96)	140.5 (5.53)	146.0 (5.75)	177.3 (6.98)	185.8 (7.31)	7.2 (0.28)	34.8 (1.37)	43.2 (1.7)
D30FN3-L05014	151.1 (5.95)	165.6 (6.52)	171.1 (6.74)	202.4 (7.97)	210.9 (8.3)	7.7 (0.30)	35.3 (1.39)	43.8 (1.72)
D30FR3-L05015	151.0 (5.95)	165.5 (6.52)	171.0 (6.73)	202.3 (7.96)	210.8 (8.3)	7.2 (0.28)	34.8 (1.37)	43.2 (1.7)

Additional information

Operating Temp	5°C -150°C (41°F -302°F) Environment Temp 0°C -40°C (32°F -104°F)
Operating Pressure	-1 – 7 barg (-14.7 – 103 psig)
Surface Roughness Product contact	Ra ≤ 0.38 µm (15 µin)
Surface Treatment	Mirror polished. Non animal origin polishing compounds are used. Dished End bottom glass blasted for a matte finish
Product contact material	L - Stainless Steel 316L/1.4404. ASME SA-479. ASTM A-182. EN 10272 (PED). UG14 or Code case 2156-1 (Other materials are available upon request)



Add-ons

	1" TOV	0.75" TOV
Option 1 Extended Butt End	ZG00514-05375	ZG00514-05385
Option 2 TC	ZG00514-05376	ZG00514-05386
Option 3 45° Elbow	ZG00514-05377	ZG00514-05387
Option 4 45° Elbow + TC	ZG00514-05378	ZG00514-05388



www.metenova.com

Phone: +46 (0)31-335 95 00 | +1(908) 537 4199 | E-mail: info@metenova.com

The information in this publication is subject to change without prior notice. The information in this document is believed to be complete and accurate at the time of publication. Metenova assumes no responsibility for any errors that may appear in this document. Customer is responsible for determining Metenova’s product will perform suitable in the intended application